



K 165

TWO WAY SYSTEM

300 W

T 24 - Tweeter:


1. 24mm diaphragm Neodymium tweeter with PEI dome, for a brilliant reproduction of high frequencies in a compact size.
2. Annular acoustic lens optimized for exceptional off-axis performance.
3. 6dB/Oct crossover integrated on tweeter wiring.
4. Mounting accessories for external or embedded mounting included.

V 165 - Woofer:


1. V-cone® design for best off-axis response, clear mid-high frequency detail and powerful bass.
2. Foam surround combining high sensitivity and deep bass response.
3. Pure copper 25mm (1 in.) voice coil woofer for high dynamic power handling.
4. High flux density 80mm (3.15 in.) ferrite magnet for a powerful undistorted sound.
5. Easy-to-install DIN size basket protected by abrasion-resistant dust paint.

TECHNICAL SPECIFICATIONS

Component	2-way system	
Size		
Woofer	mm (in.)	165 (6.5)
Tweeter diaphragm	mm (in.)	24 (0.9)
Voice Coil Ø		
Woofer	mm (in.)	25 (1)
Tweeter	mm (in.)	14 (0.55)
Power Handling		
	W peak	300
	W continuous	75
Sensitivity		
	dB SPL	93,5
Impedance		
	Ω	4
Frequency Response		
	Hz	55 ÷ 23k
Crossover		
		6 dB/Oct tweeter integrated
Weight of one component		
Woofer	kg (lb)	0,7 (1.54)
Tweeter	kg (lb)	0,03 (0.07)
Woofer Magnet		
		High density flux ferrite
Tweeter Magnet		
		Neodymium
Cone		
		Water-repellent pressed paper
Dome		
		PEI
Xmech		
	mm (in.)	±3,5 (0.14)



A	164,6 mm	6.48 in.
B	144 mm	5.67 in.
C	69 mm	2.72 in.
D	63 mm	2.48 in.



A	34 mm	1.3 in.
C	20 mm	0.8 in.
D	13 mm	0.5 in.