



K 170

TWO WAY SYSTEM

280 W

T 24 - Tweeter:


1. 24mm diaphragm Neodymium tweeter with PEI dome, for a brilliant reproduction of high frequencies in a compact size.
2. Annular acoustic lens optimized for exceptional off-axis performance.
3. 6dB/Oct crossover integrated on tweeter wiring.
4. Mounting accessories for external or embedded mounting included.

V 170 - Woofer:


1. V-cone® design for best off-axis response, clear mid-high frequency detail and powerful bass.
2. Foam surround combining high sensitivity and deep bass response.
3. Pure copper 25mm (1 in.) voice coil woofer for high dynamic power handling.
4. High flux density 80mm (3.15 in.) ferrite magnet for a powerful undistorted sound.
5. Easy-to-install DIN size basket protected by abrasion-resistant dust paint.

TECHNICAL SPECIFICATIONS

Component	2-way system	
Size		
Woofer	mm (in.)	170 (6.7)
Tweeter diaphragm	mm (in.)	24 (0.9)
Voice Coil Ø		
Woofer	mm (in.)	25 (1)
Tweeter	mm (in.)	14 (0.55)
Power Handling		
	W peak	280
	W continuous	70
Sensitivity		
	dB SPL	93,5
Impedance		
	Ω	4
Frequency Response		
	Hz	55 ÷ 23k
Crossover		
	6 dB/Oct tweeter integrated	
Weight of one component		
Woofer	kg (lb)	0,53 (1.17)
Tweeter	kg (lb)	0,03 (0.07)
Woofer Magnet		
	High density flux ferrite	
Tweeter Magnet		
	Neodymium	
Cone		
	Water-repellent pressed paper	
Dome		
	PEI	
Xmech		
	mm (in.)	±3 (0.12)



A	165 mm	6.5 in.
B	140 mm	5.51 in.
C	51 mm	2.01 in.
D	45 mm	1.77 in.



A	34 mm	1.3 in.
C	20 mm	0.8 in.
D	13 mm	0.5 in.